



**COPELAND COATING
COMPANY, INC.**



ACTION-PAVE®
ATHLETIC SURFACES

ACTION PAVE ACRYLIC HOCKEY RINK - INLINE SKATING COLOR COAT SYSTEM

DESCRIPTION -

100% acrylic emulsion, special pigmented prime color reinforcing pigments and super tough latex additives that provide a super durable, long lasting inline skating surface. The ACTION PAVE ACRYLIC HOCKEY RINK COLOR COAT SYSTEM has been specifically engineered to protect the entire ATHLETIC SURFACE from the ultraviolet rays of the sun and to cool the surface for more pleasurable play. Unlike other acrylic surfacing systems, The ACTION PAVE ACRYLIC HOCKEY RINK COLOR COAT SYSTEM is fully pigmented, resulting in longer lasting, richer, full depth color. This color coat system has been specifically made more durable to withstand the aggressiveness of inline skating and the pounding of hockey sticks.

USE -

Apply over newly paved surfaces or existing color coated surfaces. Apply over ACTION PAVE ACRYLIC RESURFACER.

APPLICATION -

Use a standard, commercial quality, squeegee or hair type applying brush 24", 30" or 36" in width. Clean squeegee/brush with water immediately after use.

MIX DESIGN -

ACTION PAVE ACRYLIC HOCKEY RINK COLOR COAT SYSTEM is concentrated and needs to be mixed on site with clean water. Thorough mixing is required. Mortar mixer offers best results.

2 parts ACTION PAVE ACRYLIC HOCKEY RINK COLOR
1 part water

COVERAGE -

USA Inline skating rinks have a size range of 85' x 100' To 145' x 200'. A two (2) coat application will require approximately .22 gallons mixed material per square yard. A one (1) coat application .12 gallons mixed material per square yard.

SURFACE PREPARATION AND APPLICATION -

The surface must be clean and free of grease, oil and any other foreign debris. The ACTION PAVE ACRYLIC HOCKEY RINK COLOR COAT SYSTEM is to be applied over previously color coated or new surfaces which have already received ACTION PAVE ACRYLIC RESURFACER.

Spread ACTION PAVE ACRYLIC HOCKEY RINK COLOR COAT evenly by walking in one direction and then reversing direction. Always maintain a wet edge and do not overwork the material. Avoid leaving any puddles when squeegeeing material back and forth. Allow materials to dry sufficiently before applying the ACTION PAVE ACRYLIC WHITE LINE PAINT.

LIMITATIONS -

- Do not apply ACTION PAVE ACRYLIC HOCKEY RINK COLOR COAT SYSTEM when surface temperature is below 50 °F(10°C) or when fog, rain or high humidity is imminent.

Page 1 of 2

3600 Route 20
PO Box 595
Nassau, (Albany area) NY 12123
www.copelandcoating.com



Tel: (518) 766-2932
(800) 303-4219
Fax: (518) 766-3603
E-mail: copeland@albany.net

"The pavement maintenance people...since 1945"



LIMITATIONS (continued) -

- Do not apply if surface temperature is above 130°F (55°).
- Do not store in direct sunlight.
- Close cover tightly.
- Keep from freezing.